

Adjustable Kraftform Torque Screwdrivers

Wera's adjustable torque screwdrivers can be adjusted in fine increments and guarantee proven quality and an ergonomic design for the benefit of the user.



Easy torque adjustment without special tools.



Easy-to-read scale value with touch indicators for scale increments.



Measurement accuracy is $\pm 6\%$ in accordance with standard EN ISO 6789.



Rapidaptor technology for rapid bit changes.



Unlimited loosening torque to loosen seized screws.



The multi-component Kraftform handle with hard and soft zones for high-speed action protects the hand and is more comfortable during intensive use.

All Wera torque tools are supplied with a calibration certificate. Our workshop offers a full service for all Wera torque tools. Please contact us with any queries regarding our service, recalibration or repairs at 1-800-267-5541.

Series 7400 Krafftform Torque Screwdrivers

With variable torque adjustment.

Series 7400 Krafftform adjustable torque screwdrivers with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN 3126-C 6,3 und E 6,3 (ISO 1173) hexagon insert bits and Wera Series 1 and 4
Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology
Accuracy: ±6 % (EN ISO 6789)
Handle: Krafftform, with anti-roll protection, multi-component

Code	Art.No.		Nm	Nm	mm			
0507470003	7440	1/4"	0.3-1.2	0.05	155	6"		1
05074701003	7441	1/4"	1.2-3.0	0.10	155	6"		1

Series 7400 Krafftform adjustable torque screwdrivers with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN 3126-C 6,3 und E 6,3 (ISO 1173) hexagon insert bits and Wera Series 1 and 4
Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology
Accuracy: ±6 % (EN ISO 6789)
Handle: Krafftform, with anti-roll protection, multi-component

Code	Art.No.		in. lbs.	in. lbs.	mm			
05074710002	7445	1/4"	2.5-11.5	0.5	155	6"		1
05074711002	7446	1/4"	11.0-29.0	1.0	155	6"		1

Series 7400 Krafftform pistol handle, adjustable torque screwdrivers with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN 3126-C 6,3 und E 6,3 (ISO 1173) hexagon insert bits and Wera Series 1 and 4
Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology
Accuracy: ±6 % (EN ISO 6789)
Handle: Krafftform, pistol handle, multi-component

Code	Art.No.		Nm	Nm	mm	mm		
05074702003	7442	1/4"	3.0-6.0	0.25	150	100	6"	4"

Series 7400 Krafftform pistol handle, adjustable torque screwdrivers with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN 3126-C 6,3 und E 6,3 (ISO 1173) hexagon insert bits and Wera Series 1 and 4
Construction: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology
Accuracy: ±6 % (EN ISO 6789)
Handle: Krafftform, pistol handle, multi-component

Code	Art.No.		in. lbs.	in. lbs.	mm	mm		
05074712002	7447	1/4"	25.0-55.0	2.5	150	100	6"	4"



Why does Wera make adjustable torque screwdrivers?



When it comes to assembly and maintenance work many screws have to be tightened with controlled torque to guarantee the safety of the screw connection and/or prevent damage to the screw or the work piece. Wera's adjustable torque screwdrivers are the perfect tools for these applications. They feature a torque range between 0.3 Nm and 8.8 Nm, two different handles, measurement accuracy of ± 6% and Rapidaptor technology for rapid bit changes.

7440/41 Kraffform Torque screwdriver set 0.3-3.0 Nm



Code			
05074738002	●	7400	1 x 7440; 1 x 7441
	○	840/1 Z Hex-Plus	1 x 2.0x25; 1 x 2.5x25; 1 x 3.0x25; 1 x 4.0x25; 1 x 5.0x25; 1 x 6.0x25
	⊗	867/1 TZ TORX®	1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
		867/1 Z IP TORX PLUS®	1 x 6 IPx25; 1 x 7 IPx25; 1 x 8 IPx25; 1 x 9 IPx25; 1 x 10 IPx25; 1 x 15 IPx25; 1 x 20 IPx25; 1 x 25 IPx25; 1 x 30 IPx25

7440/41/42 Kraffform Torque screwdriver set 0.3-6.0 Nm



Code			
05074739002	●	7400	1 x 7440; 1 x 7441
	●	7400 Pistole	1 x 7442
	○	840/1 Z Hex-Plus	1 x 2.0x25; 1 x 2.5x25; 1 x 3.0x25; 1 x 4.0x25; 1 x 5.0x25; 1 x 6.0x25
	⊗	867/1 TZ TORX®	1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
		867/1 Z IP TORX PLUS®	1 x 6 IPx25; 1 x 7 IPx25; 1 x 8 IPx25; 1 x 9 IPx25; 1 x 10 IPx25; 1 x 15 IPx25; 1 x 20 IPx25; 1 x 25 IPx25; 1 x 30 IPx25

7442/6 Installation set for tyre pressure control systems



Code			
05074737002	○	327	1 x 32
	●	7400 Pistole	1 x 7443
	●	790 A/50	1 x 11.0; 1 x 12.0
	⊗	867/1 Z TORX®	1 x TX 20x25
	○	870/1	1 x 1/4"x25